

YY-07P Composite Material Horizontal Cutting Machine 复合材料平切机

技术规格	TECHNICAL SPECIFICATION
机身尺寸: 6m × 4.3m × 2.4m(L × W × H)	Floor Size Required : L6m×W4.3m×H2.4m
平台尺寸: 3.1m × 1.6m(L × W)	Working Table Size:3.1m×1.6m(L×W)
可裁切海棉尺寸: 2.4m × 1.5m × 0.5m(L × W × H)	Foam Cutting Thickness : 2-15mm
可裁切海棉厚度: 2 mm~15mm	Working Width : 1500mm
裁切速度: 3-10 m/min	Working Length : 2400mm
平台移动马达: 2HP附减速机和变频器	Cutting And Stacking Height : 500mm
刀带马达: 3HP-6P	Working Table Size : 2700mm×1600mm
升降螺杆: 使用滚珠式德国进口螺杆	2 Sharpener Motors
上升下降马达: 2HP附减速机	Cutting Tolerance ± 0.2mm
磨刀马达: 1/8HP × 2	Static Elimination System
压辊转动:1/4HP,附有减速机	Press roller motor:1/4HP,with reducer
压辊升降:1/8HP,附有减速机	Rise/down motor:1/8HP,with reducer
电动调整同步压轮	Automatic Roller Adjustment For Height
电控制操作箱: 日本三菱PLC	Pneumatic Blade Tightener



Feature:

- Stationary cutting unit applied to cut EVA,Rubber ,EPDM,PE
- Circulating bandknife being sharpened by a motorized grinding device during the cutting procedure
- Bandknife width 50 mm; service life about 100-150 hours
- 3-digit number of automatic programmes that can be saved with pre-selection of number of number of pieces, layer thickness [0.5-15mm with increments of 0.4mm]
- Cutting angle and table speed separately adjustable for forward and backward movement
- Cutting speed infinitely adjustable [2m-10m/min]
- Table material : aluminum plate covered with vacuum system

Advantages:

- Excellent efficiency, particularly with larger amounts of sheets for complex material foams to be split horizontally
- Working Table with vacuum system which is able to hold foam material
- Stable operation table

主要用途: 本机主要用于特殊复合材料如: EVA,橡胶, EPDM, PE的切片工作