

# YY-07R

## Rigid Foam Horizontal Cutting Machine

### 硬质海绵水平式切割机

技术规格	TECHNICAL SPECIFICATION
机身尺寸: L9.5m × W3.2m × H3m	Machine Dimension: L9.5m × W3.2m × H3m
平台尺寸: L3.1m × W1.6m	Working Table Size: L3.1m × W1.6m
可切材料尺寸: L3.5m × W1.4m × H1m	Cutting Dimension: L3.5m × W1.4m × H1m
裁切速度: 0.1~3m/min	Cutting Speed: 0.1~3m/min
回板速度: 最快 25m/min	Table Return Speed: Max 25m/min
裁切公差: ±0.25mm	Cutting Tolerance: ±0.25mm
刀带: 锯齿型刀带	Blade: Bandsaw
刀带速度: 50~650m/min	Blade Rotation Speed: 50~650m/min
材料真空吸附系统: 7.5KW × 2台	Vacuum System
总功率: 25kw	Total Power: 25kw
电控制操作箱: 日本三菱PLC	Control Panel: Mitsubishi PLC
刀带马达: 10HP × 1台	Blade motor: 10HP
平台移动马达: 3HP, 附有减速机	Table moving motor: 3HP, with reducer
刀架升降马达: 3HP, 附有磁带机	Rise/down motor: 3HP, with reducer



#### Feature:

- Stationary cutting unit
- 5-digit number of automatic programmes that can be saved with pre-selection of number of pieces, layer thickness [ 2-100mm with increments of 0.5mm]
- Cutting speed infinitely adjustable [0.1-3m/min]
- Table material : aluminum plate covered with vacuum system

#### Advantages:

- Excellent efficiency, particularly with larger amounts of sheets for complex material foams to be split horizontally
- Working Table with vacuum system which is able to hold foam material
- Stable operation table

**主要用途:** 本机主要用于硬质泡沫板的切片工作

